


AVAILABLE AS
BN001GZ without battery and charger | **BN001GD201** with 2x BL4025 battery, DC40RA charger and plastic case

USER BENEFITS

- Suitable for carpenters and construction workers to build walls, roofs, decks and other structural components.
- Excellent rapid-fire performance with a pneumatic feel achieved by an air spring mechanism
- Reduced firing feedback improves control and comfort for more precise work and less fatigue
- Window for checking remaining nail quantity
- Driving depth adjustment by dial
- LED light with preglow and afterglow functions


TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Magazine capacity	58
Nail length	50-90 mm
Nail diameter	2,9-3,3 mm
Nail collation angle	30-34°
Nail type	clipped-head nails
Dimensions (L×W×H)	326 x 186 x 358 mm
Weight*	5,3 kg

** With BL4020 battery*
PRODUCT HIGHLIGHTS

Anti-slip nose
Redesigned tip shape ensures stability during angled nailing.

Anti-dry fire mechanism
Activated before the number of remaining nails reaches zero, avoiding missed shots.

Hooks
Equipped with a belt hook and a 38mm rafter hook for easy hanging on ladders, scaffolding, and timbers.


Operation mode
Single nailing / continuous nailing with contact actuation.

ACCESSORIES
Nose adapter set
1916P4-2

Extended capacity magazine set
1917P3-0

Hook
347C14-9

Rafter hook
141X57-7

Clipped-head, 50 mm
P-45783

Clipped-head, 75 mm
F-30579

Clipped-head, 83 mm
F-30601

Clipped-head, 90 mm
F-31645

NOISE AND VIBRATION

Sound pressure level: **90 dB(A)**, Sound power level: **101 dB(A)**, Vibration level: **3,6 m/s²**

COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F**
Compatible: **BL4050F, BL4080F, BL4080H**
RELATED PRODUCTS

18 V LXT DBN900
Cordless Framing Nailer

18 V LXT DBN901
Cordless Framing Nailer

18 V LXT DBN640
Cordless Metal Connector Nailer



AVAILABLE AS

UC033GZ without guide bar, saw chain, battery and charger

USER BENEFITS

- When fitted with the carbide-tipped M53RK saw chain it is capable of cutting slate, roofing materials, and tempered glass, making it an effective choice for rescue applications
- Air-filter dust cover removes without tools, making cleaning easy while keeping debris out of the machine.
- Captive nuts prevent nut loss during guide bar or saw chain replacement.
- Adjustable automatic chain lubrication with a large oil reservoir.
- Equipped with both mechanical and electric brake.

TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Max output power*1	2,7 kW
Guide bar length	450 / 500 mm
Chain pitch	0,325"
Chain saw gauge	1,3 mm
Chain speed	0-29 m/s
Oil tank capacity	260 mL
Dimensions (L×W×H)*2	952 x 303 x 280 mm
Weight*2	8,4 kg

*1 With BL4080H battery | *2 With BL4080H battery, 500 mm guide bar and M53RK saw chain

PRODUCT HIGHLIGHTS



Depth limiter
Optional depth limiter enables easy cutting-depth adjustment when performing plunge-cutting in rescue operations.



Wrap-around front handle
Enables a secure right-side grip for stable horizontal handling.



Excellent restartability under load
If the chain slows or stops due to heavy load, the saw instantly resumes cutting as soon as the load is released, with no need to retrigger.



IPX4M water and dust resistance
Built to withstand tough conditions, the saw meets the IPX4M standard for use in rainy environments when tool and battery are marked accordingly.

ACCESSORIES



Guide bar	Length	Saw chain	Type	Cover	Drive sprocket
RESCUE					
1916J8-2	500 mm	1916K0-5	M35RK	1916K3-9	1916A5-5
1915Y8-1	450 mm	1916A2-1	95TXL	-	1916A5-5
1915Y9-9	500 mm	1916A3-9	95TXL	-	1916A5-5

Depth limiter
80-230 mm
1916K2-1



Chain oil
195093-1



Guide bar tip for rescue guide bar
1412F5-6



NOISE AND VIBRATION

Sound pressure level: **100 dB(A)**, Sound power level: **108 dB(A)**, Vibration level: **4,4 m/s²**

COMPATIBILITY

Recommended: **BL4080H**

RELATED PRODUCTS



40+40 V max XGT
CE001G
Cordless power cutter



40 V max XGT
CE004G
Cordless power cutter



40 V max XGT
JR002G
Cordless reciprocating saw



40 V max XGT
GA038G
Cordless angle grinder



40+40 V max XGT
HR006G
Cordless rotary hammer

BL MOTOR XPT IPX4M



AVAILABLE AS

UC031GZ with guide bar, chain and 0,325" pitch drive sprocket and without battery and charger
UC031GZ01 with 3/8" pitch drive sprocket and without guide bar, chain, battery and charger

USER BENEFITS

- Suitable for: professional arborists, landscapers, and maintenance technicians seeking a compact, high-performance pruning solution
- Enhanced trigger response provides fast acceleration for continuous cutting
- Adjustable automatic chain lubrication and chain oil view window
- Captive nut prevents nut loss during guide bar or saw chain replacement
- Equipped with variable speed, electric and mechanical brake



TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Max output power*	1,06 kW
Guide bar length	250 / 300 mm
Chain pitch	0,325" / 3/8"
Chain saw gauge	1,1 / 1,1 mm
Chain speed	0-24 m/s
Oil tank capacity	150 ml
Dimensions (L×W×H)*2	525 x 188 x 203 mm
Weight*2	3,2 kg

* With BLA050F1 ** with BLA025 battery and 250 mm guide bar

PRODUCT HIGHLIGHTS



Excellent tool balance
 Shorter distance between the top handle and the centre of gravity improves balance and reduces arm strain, making horizontal cutting more comfortable and controlled.



Excellent restartability
 If the tool stops due to overload, it resumes cutting automatically once the load is removed—no need to press the trigger again.



Main power button with clear feedback
 Main power button and dual-colour warning lamp make it easy to recognise power status and errors, improving usability and safety



Hook
 Quick-attach hook allows fast, one-handed attachment and removal from a carabiner or similar device.

ACCESSORIES

Guide bar	Length	Saw chain	Type	Cover	Drive sprocket
191T85-8	250 mm	191T89-0	80TXL	413X66-9	1916N6-4
191G15-1	300 mm	191H01-8	90PX	-	1916N7-2
CARVING					
1911A1-3	250 mm	191G96-5	25AP	452093-7	1918C1-9

File set in roll-up pouch
D-72154



Round file bit - ø 4 mm
D-73748



Angle plate - 25/30°
D-75605



Filing vise
D-67480



Mineral oil for chain - 1l
195093-1



Spike bumper
1917P5-6



NOISE AND VIBRATION

Sound pressure level: **97 dB(A)**, Sound power level: **105 dB(A)**,
 Vibration level: **3,1 m/s²**

COMPATIBILITY

Recommended: **BL4025** and **BL4040/F**
 Compatible: **BL4020** and **BL4050F**

RELATED PRODUCTS



40 V max XGT
UC029G
 Cordless pruning saw - 150 mm



40 V max XGT
UA004G
 Cordless telescopic pole saw - 300 mm



40 V max XGT
UC026G
 Cordless chain saw - 400 mm



AVAILABLE AS

UB004GZ01 without battery and charger

USER BENEFITS

- Blowing power comparable to 65 cc class engine blowers when equipped with BL4080H battery
- Ideal for clearing debris from large areas such as parkings, parks, sidewalks...
- Runtime of ~30 min with BL4080H battery, operating in high mode and frequent trigger operation while moving
- 40% lighter compared to our previous model



TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Max. blowing force*1	32 N
Max. air velocity*1	96 m/s
Max. air volume*1	19,1 m ³ /min
Dimensions (L×W×H)	242 x 585 x 522 mm
Weight*2	5,8 kg

*1 With BL4080H battery | *2 With BL4020 battery

PRODUCT HIGHLIGHTS



Compact storage solution

The pipe can be secured upright on top of the harness, reducing the amount of storage space required.



Adjustable

Control stick can be adjusted 180 mm forward and back and 90° left or right while the telescopic pipe offers a stepless length adjustment within a range of 250 mm.



2 battery system

The blower runs on one battery and switches to the second one when the first one runs out.



Cruise control

Locks the trigger at a desired position to reduce hand fatigue during long continuous operation.



NOISE AND VIBRATION

Sound pressure level: **81,2 dB(A)**,
Sound power level: **94,4 dB(A)**, Vibration level: **0.2 m/s²**



COMPATIBILITY

Recommended: **BL4040F, BL4050F, BL4080F, BL4080H**
Compatible: **BL4020, BL4025, BL4040**

ACCESSORIES

End nozzle
4134R4-7



Wide end nozzle
1918E9-7



Flat nozzle
413Y09-7



Cushion belt
1917R2-6



Battery holder
for the belt
1917R0-0



RELATED PRODUCTS



40 V max XGT
UB001G

Max. blowing force 0-12 / 17 N
Max. air velocity 0-53 / 64 m/s
Max. air volume 0-13,5 / 16 m³/min



40 V max XGT
UB003G

Max. blowing force 0-16 N
Max. air velocity 0-68 m/s
Max. air volume 0-13,8 m³/min



40 V max XGT
UB005G

Max. blowing force 0-5,0 N
Max. air velocity 0-87 m/s
Max. air volume 0-3,5 m³/min



40 V max XGT
UB002G

Max. blowing force 0-3,2 N
Max. air velocity 0-99 m/s
Max. air volume 0-3,6 m³/min



AVAILABLE AS

UG001GZ without battery and charger

USER BENEFITS

- Suitable for professional landscapers, grounds maintenance teams and property owners who need efficient, low-fatigue grass cutting over large areas such as parks, sports fields, roadsides and facility grounds
- Three-facet-ground teeth with curved tips reduce friction and maintain cutting performance, even when sap accumulates on the blades
- A durable, abrasion-resistant metal underplate allows smooth ground-sliding trimming
- Large front and rear wheels ensure smooth travel over uneven ground and easier handling without lifting
- Featuring soft start, constant speed control and anti-restart function



TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Cutting width	500 mm
Cutting height adjustment	25-105 mm
Strokes per minute	3.000 / 4.000 min ⁻¹
Dimensions (L×W×H)	1.345 x 521 x 791 mm
Weight* ²	10,0 kg

* With BL4040F battery

PRODUCT HIGHLIGHTS



Wide 500 mm cutting efficiency

The 500 mm T-shaped shear blade allows fast, straight-line cutting by simply pushing forward, improving productivity over wide areas without side-to-side swinging and reducing operator fatigue.



Tool-less handle height adjustment

A three-position, tool-less handle height adjustment enables comfortable operation for different user heights, improving control, reducing fatigue and supporting efficient, extended use.



Tool-less cutting-height adjustment

Stepless, tool-less cutting height adjustment from 25 to 105 mm allows quick adaptation to different grass conditions and applications, ensuring consistent cutting results with minimal setup time.



Compact storage

A foldable handle allows the tool to be stored upright or horizontally in a compact form. This space-saving design makes transport easier and enables convenient storage in small sheds, workshops or vehicle compartments.

ACCESSORIES

Shear blade, 500 mm
1916X3-0

Shear blade, 330 mm
1912V6-6



NOISE AND VIBRATION

Sound pressure level: **73 dB(A)**, Sound power level: **90 dB(A)**,
Vibration level: **0.9 m/s²**



COMPATIBILITY

Recommended: **BL4020, BL4025, BL4040, BL4040F, BL4050F, BL4080F, BL4080H**

RELATED PRODUCTS



40 V max XGT
UX01G
Cordless multi
function power head



1913C9-3
Ground trimmer
attachment
EN424MP - 330 mm



SIAEN425MP
Ground trimmer
attachment
EN425MP - 500 mm



40 V max XGT
UR002G
Cordless grass
trimmer - 350 mm



40 V max XGT
UR013G
Cordless grass
trimmer - 450 mm


AVAILABLE AS

PB003GZ without battery and charger

USER BENEFITS

- Quiet, cold-cut operation enables fast, high-precision performance with minimal sparks, delivering clean, straight results ideal for pipes, tubes, conduits and metal bars used in plumbing, electrical and HVAC work.
- Large tool hook for hanging the tool on ladders.
- Tool-free blade changes for quick and easy swaps.
- Four LEDs job light with pre-glow and afterglow functions
- Equipped with variable speed, constant speed, electric brake and anti-restart functions


TECHNICAL SPECIFICATIONS

Accumulator voltage	40 V max XGT
Blade speed	0-3,2 m/s
Blade (L×W)	835x13 mm
Blade thickness	0,5 mm
Cutting capacity of square pipe	66x66 mm
Cutting capacity of round pipe	66 mm
Dimensions (L×W×H)*	392 x 175 x 244 mm
Weight*	4,0 kg


* With BL4020 battery

PRODUCT HIGHLIGHTS


Apply blade wax before cutting
Reduces friction, improves performance and extends blade life



Adjustable stopper plate
Provides improved workpiece support while cutting and can be adjusted without the use of tools.



Stand (optional)
The stand features a slanted clamping vise that ensures secure and stable cutting. Cutting capacity with stand: round pipe 55 mm, square pipe 55x55 mm.

Dial	Speed	Application
1	1,3 m/s	Stainless steel, alloy steel
2	1,5 m/s	Steel materials (solid round bar, structural steel, thick steel pipe, etc.)
3	2,1 m/s	
4	2,5 m/s	
5	2,9 m/s	Steel materials (thin steel pipe, etc.)
6	3,2 m/s	


NOISE AND VIBRATION

 Sound pressure level: **82 dB(A)**, Sound power level: **90 dB(A)**, Vibration level: **1,4 m/s²**

COMPATIBILITY

 Recommended: **BL4020, BL4025, BL4040, BL4040F**
 Compatible: **BL4050F, BL4080F, BL4080H**
ACCESSORIES

 Stand
1917F0-6

 Cutting wax
191897-9

 Grip
158237-4

 Band saw blades
BiM (5 pcs)


Code	No. of teeth	Width	Material
B-40543	14	3-6 mm	Plastics and non-ferrous metal. Mild steel, cast steel and cast iron. Hard steel and stainless steel.
B-40559	18	2-3 mm	
B-40565	24	<2 mm	

RELATED PRODUCTS

 40 V max XGT
PB002G
Cordless Portable
Band Saw

 18 V LXT
DPB183
Cordless Portable
Band Saw

 40 V max XGT
CS002G
Cordless Metal
Cutter

 40 V max XGT
JR002G
Cordless Recipro
saw

 40 V max XGT
GA055G
Cordless Flat-head
Angle Grinder